

17.13 HEIGHTS AND AREA EXCEPTIONS. The regulations contained herein relating to the height of buildings and the size of yards and other open spaces shall be subject to the following exceptions:

- (a) Churches, schools, hospitals, sanitariums, and other public and quasi-public buildings may be erected to a height not exceeding sixty (60) feet nor five (5) stories, provided the front, side and rear yards required in the district in which such building is to be located are each increased by a length equal to the increased height.
- (b) Chimney, cooling towers, elevator bulkheads, fire towers, monuments, penthouses, stacks, scenery lofts, tanks, water towers, ornamental towers, spires, wireless, television or broadcasting towers, masts or aerials; microwave radio relay structures; telephone, telegraph and power poles and lines and necessary mechanical appurtenances are hereby excepted from the height regulations of this Code and may be erected in accordance with other regulations or codes of the Village.
- (c) Residences in the residential district may be increased in height by not more than ten (10) feet when all yards and other required open spaces are correspondingly increased by a length equal to the increased height.
- (d) Where a lot abuts on two (2) or more streets or alleys having different average established grades, the higher of such grades shall control only for a depth of one hundred twenty (120) feet from the line of the higher average established grade.
- (e) Buildings on through lots and extending from street to street may have waived the requirements for a rear yard by furnishing an equivalent open space on the same lot in lieu of the required rear yard provided that the setback requirements on both streets be complied with.
- (f) Where a lot has an area less than the minimum number of square feet per family required for the district in which it is located and was of record as such at the time of the passage of this Code, such lot may be occupied by one (1) family.
- (g) Every part of a required yard shall be open to the sky, unobstructed, except for accessory buildings in a rear yard, and the ordinary projections of sills, belt courses, cornices and ornamental features projecting not more than twelve (12) inches.
- (h) Open or enclosed fire escapes and fire towers may project into a required yard not more than five (5) feet and into a required court not more than three and one-half (3-1/2) feet, provided it be so located as not to obstruct light and ventilation.